

REMS Tiger ANC pneumatic

Pneumatic reciprocating pipe saw

Powerful, robust, handy compressed air tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Ideal for use in dangerous, e.g. in wet environment. For assembly, dismantling, repair.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger ANC SR with electronic stroke speed control.

REMS Tiger pneumatic – for sawing in dangerous environment.

Saws effortless, fast, right-angle. Unique guide support for 400% additional sawing force.

Sturdy, square lift rod. Oscillating drive with ANC.

Aggressive orbital action for fast feed forward sawing and long service life of saw blades. Universal saw blade clamp.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.8 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward during free-hand sawing. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful pneumatic motor with ample reserve capacity, 1000 W. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Operating pressure 6 bar, air consumption $\leq 1.6 \text{ m}^3/\text{min}$. Safety switch with lock.

Additional description see REMS Tiger ANC, page 60–61.



German Quality Product

Supply format

REMS Tiger ANC pneumatic Set. Pneumatic reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful pneumatic 1000 W, operating pressure 6 bar, safety switch with lock. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Air inlet hose, air outlet hose. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

| | |
|--|----------|
| | Art.-No. |
| | 560022 |

Accessories

| Description | Art.-No. |
|---|----------|
| REMS saw blades see page 64–65. | |
| REMS Tiger ANC pneumatic drive unit | 560002 |
| Guide support 2" , for pipes $\varnothing \frac{1}{2}$ –2" | 563000 |
| Guide support 4" , for pipes $\varnothing 2\frac{1}{2}$ –4" | 563100 |
| Guide support 6" , for pipes $\varnothing 5$ –6" | 563200 |
| Dual purpose holder for sawing and threading, with REMS Tiger ANC and REMS Amigo E, Amigo, Amigo 2 | 543100 |
| Protective cap for guide support 2" , 4" and 6", for clamping of thin-walled material | 563008 |
| Steel case | 566051 |



3.8 kg 1000 W 6 bar

